

Part No. 99-0144

TC75

Riveting tool with proces control for installation of lockbolts and structural blind rivets

Scope of use:

Type of rivet	SRB (Lockbolt) Standard		SRB (Lockbolt) Multigrip		Hucktainer Plus	Blind rivets
Ø of the rivet	5	6/6.4	5	6.4	10	6.4*
Aluminium	✓	✓	✓	✓		✓
Steel	✓	✓	✓	✓		✓
Stainless	✓	✓				✓

^{*}structural blind rivets: TIBULB, M-LOCK, MAGNA-BULB, HUCKLOCK etc.

Technical parameters:

Model	TC 75	
Pulling Force	22 kN / 6 bar	
Working Stroke	16 mm	
Weight	2.8 kg	
Force / Weight Ratio	10 kN/kg	
Length	306 mm	
Height	330 mm	
Air Consumption	2.8 litres / rivet	
Working Air Pressure	7 bar	
Hose Connection	Ø 6 mm (G 1/4")	



Description:


integrated TC system which together with evaluation of the KRB unit ensures the perfect tool for monitoring and evaluation of the riveting process

TC system indicates:

- Missing rivet
- Wrong type of rivet
- Damaged rivet
- Missing material
- Wrong setting of rivet
- Wrong alignment of material
- Damaged or defective equipment
- chip for automatic evaluation adjustment in evaluation unit
- high output and reliability verified in practice
- speed damper
- removable collecting container or rubber boot
- low noise
- simple operation
- ergonomic handle is comfortable to hold
- low transferred vibrations
- rotating air joint connection
- air intake can be moved to suit either left or right handed operator
- base cover prevents damage to workpiece
- balancer hook
- safety over-pressure dump valve
- non slip base







Standard accessories:

Description	Part No.
Air Joint Assembly	87-0281
Kit for Refilling of Oil	87-0187

Optional accessories:

Description	Part No.
Hydraulic Oil for Tool - 1 Litre	87-0188
KRB 010	99-0147
Connecting Cable 3 m	87-0295

